

RFS Technologies and SOLiD Participate in DAS Feasibility Study in Nuclear Facility: EPRI Evaluates Connectivity Alternatives to Wi-Fi

High Performance Radiating Cable Improves LTE-based Wireless Coverage



RFS Technologies and SOLiD Participate in DAS Feasibility Study in Nuclear Facility: EPRI Evaluates Connectivity Alternatives to Wi-Fi

Summary

The implementation of wireless networks within nuclear power plants could allow for greater process efficiency and enhance safety by enabling mobile work management with online connectivity. Nuclear power plants, however, have had limited success installing conventional wireless networks (Wi-Fi) inside the power block due to radio frequency (RF) coverage issues and the extensive backhaul required, driving the need for alternate solutions.

The Electric Power Research Institute (EPRI) has been exploring one potential solution – a distributed antenna system (DAS) network – through a demonstration at a currently decommissioning nuclear plant. The demonstration included testing in the 700 MHz and 2.1 GHz LTE bands to evaluate RF propagation by a DAS using radiating cables.

Introduction

Nuclear power plants are complex facilities with thousands of components. Maintenance at these sites can be challenging. Procedures are layered with multiple checks and balances – and redundancies – to meet safety and security requirements. Maintenance workers typically carry procedural guides in three-ring binders into the field, and paperwork must be completed and signed off during the process. This analog process is inefficient and does not capitalize on digital technology advances.

Mobile work management could provide numerous advantages, but it is difficult to outfit a nuclear plant with the necessary communications infrastructure to support reliable connectivity.



Photo supplied by EPRI

Wireless network installation and operation are extremely challenging in nuclear plant due to forbidding conditions such as high temperatures, radiation, metallic pressure vessels and piping, multiple elevations, and thick concrete walls reinforced with rebar.

A successful wireless network would enable on-site consultation with procedural guidance, data entry by workers in the field using tablets, and communications with managers whose signatures are needed to approve and close out work packages.

Online data would also enable remote, real-time monitoring of equipment operations and calibrations. The resultant digital workflow guidance could improve productivity and work quality while reducing costs.

Nuclear plants have had limited success with conventional Wi-Fi inside the power block. Installations are costly due to a large number of hot spots and the infrastructure needed to provide adequate coverage. The higher temperature and radiation environment also proves challenging for the wireless infrastructure, resulting in reliability

concerns and frequent component replacements. Signal performance is also challenging due to the presence of metallic pressure vessels and piping, multiple elevations with various components and equipment, and thick concrete walls reinforced with rebar




Photo supplied by SOLiD

SOLiD provided a modular, hot-swappable DAS solution designed to withstand harsh environments. The SOLiD platform allows additional services to be added on a similar network, and modules can be readily replaced to ensure high network uptime.

RFS Technologies and SOLiD Participate in DAS Feasibility Study in Nuclear Facility: EPRI Evaluates Connectivity Alternatives to Wi-Fi

The Solution

To address these issues, EPRI investigated how other industries were transmitting data wirelessly, including the mining industry, underground transportation, military, and the shipping industry. These investigations identified a distributed antenna system built for the Boston subway system's complex underground tunnel network that exhibited favorable performance.

EPRI researchers believed such a DAS system could be adapted into a nuclear environment to provide more reliable coverage and capacity with less overall power and maintenance. While there has been some historical use of DAS systems for niche applications in the nuclear industry, a DAS network had not been systematically tested and evaluated inside a nuclear plant for coverage performance at the critical LTE RF frequencies. To prove the concept, EPRI About EPRI obtained approval to conduct

field testing at a nuclear plant. The site is currently in the early stages of decommissioning, which enabled installation and testing, but imposed a tight schedule. EPRI worked with Radio Frequency Systems and SOLiD to design and test the system.

In developing the system, RFS supplied the cabling technology and support, and SOLiD provided the platform with the DAS equipment. SOLiD helped determine hardware requirements in a site walk of the station prior to field testing; they generated software models to design the system and estimate signal coverage. SOLiD ensured the testing conducted would not interfere with existing technologies essential to running the plant, such as the two-way radios used for communications between workers. The modeling exercise helped SOLiD estimate the power, length and type of cable needed. Those calculations were then tested against reality in the on-site pilot.

The SOLiD solution components are designed to withstand harsh environments that include high temperatures, water and dust. The platform is also modular and hot swappable so that additional services such as wireless carriers and public safety systems, including plant security two-way radios and outside agency Land Mobile Radios (LMRs), can be quickly added on a single network; similarly, modules are easily replaceable to ensure high network uptime.



About EPRI

The Electric Power Research Institute, Inc. (EPRI, www.epri.com) conducts research and development relating to the generation, delivery and use of electricity for the benefit of the public. An independent, nonprofit organization, EPRI brings together its scientists and engineers as well as experts from academia and industry to help address challenges in electricity, including reliability, efficiency, affordability, health, safety and the environment. EPRI's members represent approximately 90 percent of the electricity generated and delivered in the United States, and international participation extends to more than 30 countries. EPRI's principal offices and laboratories are located in Palo Alto, Calif.; Charlotte, NC; Knoxville, Tenn.; and Lenox, Mass.

About SOLiD

SOLiD (<http://www.solid.com>) helps people stay connected and safe in a rapidly-changing world through a portfolio of RF Amplifier, RF Radio and Optical Transport solutions. SOLiD enables indoor and outdoor cellular and public-safety communications at some of the world's best-known and most challenging venues including leading hospitals; professional, and college sports venues; government, university and Fortune 500 corporate buildings and campuses; international airports and metropolitan subways. For further information on SOLiD DAS, Small Cell Backhaul and C-RAN Fronthaul solutions, go to www.solid.com or call 888-409-9997.

RFS Technologies and SOLiD Participate in DAS Feasibility Study in Nuclear Facility: EPRI Evaluates Connectivity Alternatives to Wi-Fi



Photo supplied by EPRI

RFS Technologies and SOLiD were able to coordinate and deploy products for field testing on a very tight schedule before the plant was fully decommissioned.

Lastly, the SOLiD solution supports a flexible “mix-and-match” architecture whereby a common head end can feed any combination of 1W, 5W and 20W amplifiers so the network can be optimally designed to enable coverage in numerous buildings in the most efficient manner, including the containment building, offices and cafeteria. Even the best signaling power is only as good as the cable that carries it. SOLiD worked with RFS to supply the optimal conduit for distributing a clear signal throughout the facility. The two companies have a proven track record working together on projects for various environments. This project needed a radiating cable solution without stop bands

to accommodate a high most efficient manner, including the containment building, offices and cafeteria. Even the best signaling power is only as good as the cable that carries it. SOLiD worked with RFS to supply the optimal conduit for distributing a clear signal throughout the facility. The two companies have a proven track record working together on projects for various environments. This project needed a radiating cable solution without stop bands to accommodate a high performance, future-proof design and fewer shadow areas. RFS’ RADIAFLEX® “leaky feeder” coaxial cable solution made it possible to enable LTE technology for data management.

Its patented higher-order mode suppression technique allows some cable variations to have no stop band from 698-2700 MHz. RADIAFLEX radiating cables act as distributed antennas, allowing operators to scale and tailor RF coverage in even the most challenging metro, rail and road tunnels and indoor environments.

EPRI wanted the system to achieve the same threshold standard as cellular companies, aiming for 95 decibel millowatts (dBm) or higher signal strength. Data transmissions were tested at 730 MHz and at 2130 MHz frequencies to compare performance differences at high and low frequencies. At 730 MHz, an acceptable signal was generated with ~80% coverage at the target level, through as many as three walls in the plant. On the 2130 MHz test, signal strength only reached about ~35% at the target level. This proved that penetration of signal strength at lower frequencies is significantly better than the higher frequencies, at an acceptable coverage level. Additionally, results of the study indicate that 100% coverage is possible given rerouting of cable and/or use of antennas to boost signal strength in the low coverage areas. The advantage the radiating cable provided was a uniform distribution of RF energy over the entire distance of the cable

“ Successful DAS deployment in the power industry can be widely beneficial to utilities. The ability to have connectivity for mobile work management and continuous online monitoring of components could increase productivity at nuclear, coal, and natural gas facilities. ”

Nick Camilli
Electric Power Research Institute, Inc.

RFS Technologies and SOLiD Participate in DAS Feasibility Study in Nuclear Facility: EPRI Evaluates Connectivity Alternatives to Wi-Fi

Conclusion

The tests demonstrated that a DAS utilizing high-performance radiating cable can substantially improve LTE-based wireless coverage within dense concrete and steel facilities when utilizing the low frequency bands. EPRI is producing a detailed technical report to share the results of this field test with its nuclear members so they can utilize the findings to expand their mobile workforce capabilities.

Future deployment of similar DAS systems could allow nuclear power plants to identify maintenance needs proactively through support of both data and voice applications on a single network platform. This would further enhance the reliability of these facilities, enabling identification of potential problems before they reach a failure point.

This information can also be used to assess this communications technology for use in other power plant environments, including coal and natural gas-fired facilities. This technology could open the doors to other applications, such as continuous online monitoring and mobile work management



Photo supplied by EPRI

A wireless network can support productivity gains and reduced costs for power and utility plants by enabling on-site consultation, data entry, and communications as well as remote equipment monitoring.

About RFS Technologies

About RFS Technologies RFS Technologies, an Amphenol Company, is a leading designer and manufacturer of premium cable, antenna, and connectivity solutions that support wireless communications, utilities, transportation, mining, public safety, and other critical infrastructure markets throughout North America. The company provides complete RF infrastructure solutions, including coaxial cables, radiating cables, hybrid cables, waveguides, connectors, and accessories, serving distributors, system integrators, network operators, OEMs, and installers.

Building on more than a century of RF engineering expertise, RFS Technologies combines innovative product development with advanced manufacturing capabilities to deliver reliable, high-performance solutions for today's evolving communications networks. As part of Amphenol Corporation, one of the world's largest providers of high-technology interconnect, sensor, and antenna solutions, RFS Technologies benefits from global engineering resources, world-class manufacturing, and a commitment to continuous innovation.

RADIAFLEX™ : The Optimal Confined-Coverage Solution

A unique broadband solution, ensuring the most future-proof confined coverage installation

Wireless has made the move indoors– RADIAFLEX® is an important part of the solution

RADIAFLEX® is the world’s leading, leading feeder’ cable solution. Designed to provide contoured RF indoor coverage, RFS RADIAFLEX® cable provides a scalable and practical means of tailoring RF coverage in even the most challenging of confined spaces.




Future-proof confined coverage
RADIAFLEX® is a unique broadband solution, ensuring the most future-proof confined coverage installation.

Broadband solution– RADIAFLEX® supports a major services from 75 MHz to 6 GHz and is therefore optimally suited for multi-operator and multi-band applications.

Flame and fire retardancy– RADIAFLEX® cable is a low-smoke and halogen-free cabling solution that meets a major international flame- and fire-retardancy standards.

Low loss– Featuring low longitudinal and coupling losses, RADIAFLEX® is available with optional vario coupling loss configurations for longer installation runs.

Comprehensive range– With diameters spanning 1/2-inch to 1 5/8-inch, the RADIAFLEX® family is available in a broad selection of jacketing, coupling losses and bending radii.



RADIAFLEX® is available in eight distinct series:

ALF/RLF series– Heavy-duty wideband radiating cable for multi-use applications in tunnels of all kinds

RLK series – Low coupling loss radiating cable for tunnel and building applications

RLV (VARIO) series – Variable or staged coupling loss radiating cable that provides for nearly constant system loss and low amplitude variation

RAY series – Optimized for high-frequency and digital in-building and tunnel applications, where low coupling loss is required

RCF series – Small bending radii, corrugated outer radiating cable for heavy-duty applications in buildings and underground mines

RSF series– Flexible, corrugated outer radiating cable solution for in-vehicle applications

RE60 series– Worldwide unique RE60 radiating waveguide which is the leading edge solution for in-tunnel wireless applications in the 5-6 GHz band

RHCA series– Plenum-rated air-dielectric radiating cable for use in buildings where the highest standard of flame- and fire retardance

Tailor-made Cables– Cables engineered to meet new or special customer requirements

