

Coaxial Adapter 4.3-10 Female - N Female with right angle

Coaxial Adapter 4.3-10 Female - N F FEATURES / BENEFITS	emale with right	36. 7REF. SW16. 0 SW12. 0 5/8"-24UNEF-2A
External Document Links		Notes
Technical features		
STRUCTURE		
Product Line		Coaxial Cable Components
Product Type		Coaxial Adapter
MECHANICAL SPECIFICATIONS		
Connector A		4.3-10 Female
Center Contact Connector A		Copper Alloy, silver plated
Outer Contact Connector A		Copper Alloy, CuSnZn plated
Connector B		N Female
Center Contact Connector B		Copper Alloy, silver plated
Outer Contact Connector B		Copper Alloy, CuSnZn plated
Dielectric		PTFE
Sealing class		IP68, connected
ELECTRICAL SPECIFICATIONS		
Frequency Range - MHz		DC - 6000
VSWR, Return Loss	VSWR (dB)	DC TO 2 GHz VSWR 1.05 (32.25) 2 TO 3 GHz VSWR 1.08 (28.3) 3 TO 6 GHz VSWR 1.12 (24.94)
Insertion Loss, dB (Max)	dB	0.05
3rd Order IM Product @ 2x20 Watts	dBc	< -163
TEMPERATURE SPECIFICATIONS		
Operation Temperature	°C (°F)	-40 to 85 (-40 to 185)
PACKAGING INFORMATION		
Package Quantity		1

 $\mathsf{REV}:\mathsf{A}$

REV DATE: 31 Jan 2024

43F-R-NF

www.rfstechnologies.com