

4.3-10 Male Connector for 1/2" Coaxial SuperFlexibleCable, OMNI FIT™ standard

OMNI FIT™ high performance connectors are designed for use with both CELLFLEX® (copper) and CELLFLEX® Lite (aluminum) cables. They are designed specifically to provide the highest quality connector-cable interface while simplifying and speeding up connector attachment. All RFS Technologies connectors are fully tested for mechanical and electrical compliance to industry specifications. The 4.3-10 connector is an innovative, space-saving RF connection meeting all requirements even under the most severe environmental conditions and not relying on coupling nut torque to meet PIM performance.

FEATURES / BENEFITS

- Cost effective two-piece design for safe and easy installation
- Robust mechanical design for low and consistent intermodulation performance i.e. keeps the mobile network performance up, reduces the number of dropped calls and avoids revenue losses
- Standard electrical performance for consistent and repeatable VSWR i.e. ensure network system performance
- Waterproof to IP 68 i.e. no downtime risk, secures revenue
- RoHS (EU) compliant i.e. can be used on a global basis



43M-SCF12-C03

Technical features

GENERAL SPECIFICATIONS

Transmission Line Type	Coaxial Cable
Cable Size	1/2
Cable Type	Foam Dielectric Superflexible
Model Series	SCF12-50 Series
Connector Interface	4.3-10
Connector Type	OMNI FIT™ Standard
Sealing Method	O-ring
Gender	Male

ELECTRICAL SPECIFICATIONS

Nominal Impedance, ohms	Ohm	50
3rd Order IM Product @ 2x20 Watts	dBc	-162 ; typical -166
Maximum Frequency	GHz	6.0
VSWR, Return Loss	VSWR (dB)	0 < $f \le 1.0$ GHz: 1.03 (36.6) 1.0 < $f \le 2.7$ GHz: 1.04 (34.1) 2.7 < $f \le 3.7$ GHz: 1.08 (28.3) 3.7 < $f \le 5.0$ GHz: 1.10 (26.4) 5.0 < $f \le 6.0$ GHz: 1.25 (19.1)

MECHANICAL SPECIFICATIONS

Plating Outer/Inner		Trimetal/Silver
Length	mm (in)	43.9 (1.73)
Outer Diameter	mm (in)	25 (1)
Inner Contact Attachment		Basket
Outer Contact Attachment		Rigidity impaction

43M-SCF12-C03 REV : B REV DATE : 07 Oct 2018 www.rfstechnologies.com




4.3-10 Male Connector for 1/2" Coaxial SuperFlexibleCable, OMNI FIT™ standard

ACCESSORIES Wrench size front mm (in) 18 (3/4) Wrench size rear mm (in) 18 (3/4) Trimming Tool TRIM-SET-S12-C02

TESTING AND ENVIRONMENTAL

Waterproof Level	IP68



43M-SCF12-C03 Outline Drawing

External Document Links Installation Instruction Notes

43M-SCF12-C03 REV : B REV DATE : 07 Oct 2018 www.rfstechnologies.com