

7-16 DIN Female Connector for 1/2" Coaxial Cable, OMNI FIT™ standard, O-ring sealing

OMNI FIT™ high performance connectors are designed for use with both CELLFLEX® (copper) and CELLFLEX® Lite (aluminum) cables. They are designed specifically to provide the highest quality connector-cable interface while simplifying and speeding up connector attachment. All RFS Technologies connectors are fully tested for mechanical and electrical compliance to industry specifications.

The 7-16 connector is the most rugged RF connection meeting all requirements even under the most severe environmental conditions.

FEATURES / BENEFITS

- Cost effective two-piece design for safe and easy installation
- Compatible with copper and aluminium cable types i.e. one connector for both outer conductor materials eliminates the risk of faulty connector installation and helps to keep inventory down
- Robust mechanical design for low and consistent intermodulation performance i.e. keeps the mobile network performance up reduces the number of dropped calls and avoids revenue losses
- Superior electrical performance for consistent and repeatable VSWR i.e. ensure network system performance
- Waterproof to IP 68 i.e. no downtime risk, secures revenue
- RoHS (EU) and CRoHS (China) compliant i.e. can be used on a global basis



716F-LCF12-C03

Technical features

CEN	FRAI	CDE	"IEIC	אוכ

Transmission Line Type		Coaxial Cable				
Cable Size		1/2				
Cable Type		Foam Dielectric			Radiating	
Model Series		LCF12-50 Series	ICA12-50 Series F		RCF12-50 Series	
Connector Interface		7-16 DIN				
Connector Type		OMNI FIT™ Standard				
Sealing Method		O-ring				
Gender		Female				

ELECTRICAL SPECIFICATIONS

Nominal Impedance, ohms	Ohm	50
3rd Order IM Product @ 2x20 Watts	dBc	-157 ; typical -160
Maximum Frequency	GHz	6.0
		0 < f ≤ 1.0 GHz: 1.03 (36.6)
		1.0 < f ≤ 2.7 GHz: 1.04 (34.1)
VSWR, Return Loss	VSWR (dB)	2.7 < f ≤ 3.7 GHz: 1.08 (28.3)
		3.7 < f ≤ 5.0 GHz: 1.15 (23.1)
		5.0 < f ≤ 6.0 GHz: 1.25 (19.1)

MECHANICAL SPECIFICATIONS

Plating Outer/Inner		Trimetal/Silver
Length	mm (in)	51.8 (2)
Outer Diameter	mm (in)	29 (1.14)
Inner Contact Attachment		Spring Finger
Outer Contact Attachment		Spring C-Ring

716F-LCF12-C03 REV : B REV DATE : 14 Oct 2025 **www.rfstechnologies.com**




7-16 DIN Female Connector for 1/2" Coaxial Cable, OMNI FIT™ standard, O-ring sealing

Wrench size front mm (in) 20 (0.79) Wrench size rear mm (in) 20 (0.79) Trimming Tool TRIM-SET-L12-C02

TESTING AND ENVIRONMENTAL

Waterproof Level IP68



716F-LCF12-C03 Outline drawing

External Document Links Installation instruction

Notes

716F-LCF12-C03 REV : B REV DATE : 14 Oct 2025 **www.rfstechnologies.com**