

#### PRODUCT DATASHEET

## 716MR-SCF12-D01

7-16 DIN Male Connector for 1/2" Coaxial Cable, OMNI FIT™ Premium, Right Angle, threaded gasket and 360° compression sealing

OMNI FIT™ high performance connectors are designed for use with both CELLFLEX® (copper) and CELLFLEX® Lite (aluminium) cables. They are designed specifically to provide the highest quality connector-cable interface while simplifying and speeding up connector attachment. All RFS Technologies connectors are fully tested for mechanical and electrical compliance to industry specifications.

The 7-16 connector is the most rugged RF connection meeting all requirements even under the most severe environmental conditions. Sealing against outer conductor and jacket by means of threaded gasket and 360° compression fit. Multifunctional, self-lubricating HighTech polymer assembly locks on cable corrugation, avoids electrochemical potential differences and compression-fits to the jacket.



OMNI FIT™ Premium Connectors

#### **FEATURES / BENEFITS**

- Ultra high PIM performance i.e. reduced interference leading to high customer satisfaction
- Two-piece design i.e. visual inspection of interlocking leads to improved installation security
- OMNI FIT™ concept i.e. streamlined order management and reduced stock level
- Watertight sealing in mated and unmated condition, i.e. reduced efforts during installation and improved security during operation
- Unique NiTin plating i.e. extreme resistance against corrosion even under hardest climatic and environmental circumstances
- Multi-thread (Tristart) design i.e. simplified and accelerated tightening process
- RoHS (EU) and CRoHS (China) compliant i.e. can be used on a global basis

# **Technical features**

#### **GENERAL SPECIFICATIONS**

Transmission Line Type	Coaxial Cable
Cable Size	1/2
Cable Type	Foam Dielectric Superflexible
Model Series	SCF12-50 Series
Connector Interface	7-16 DIN
Connector Type	OMNI FIT™ PREMIUM Right Angle
Sealing Method	Threaded Gasket + 360° Compression
Gender	Male

## **ELECTRICAL SPECIFICATIONS**

Nominal Impedance, ohms	Ohm	50
3rd Order IM Product @ 2x20 Watts	dBc	-163 ; typical -167
Maximum Frequency	GHz	3.7
VSWR, Return Loss	VSWR (dB)	0 < $f \le 1.0$ GHz: 1.03 (36.6) 1.0 < $f \le 2.2$ GHz: 1.04 (34.2) 2.2 < $f \le 2.7$ GHz: 1.06 (30.7) 2.7 < $f \le 3.7$ GHz: 1.13 (24.3)

716MR-SCF12-D01 REV : F REV DATE : 10 Jan 2014 www.rfstechnologies.com



## PRODUCT DATASHEET

# 716MR-SCF12-D01

7-16 DIN Male Connector for 1/2" Coaxial Cable, OMNI FIT™ Premium, Right Angle, threaded gasket and 360° compression sealing

# MECHANICAL SPECIFICATIONS Plating Outer/Inner NiTin/Silver Length mm (in) 67 (2.64) Outer Diameter mm (in) 42.7 (1.68) Inner Contact Attachment Spring Finger

#### **ACCESSORIES**


Wrench size front	mm (in)	22 (7/8)
Wrench size rear	mm (in)	18 (7/10)

360° clamping

# **TESTING AND ENVIRONMENTAL**

**Outer Contact Attachment** 

Waterproof Level	IP68
Water proof Level	11 00



External Document Links Installation Instruction

Notes

**716MR-SCF12-D01** REV : F REV DATE : 10 Jan 2014 **www.rfstechnologies.com**