PRODUCT DATASHEET

BA1010-2





These antennas feature a very broad frequency band and rugged construction. Radiating elements are constructed of copper alloy, encased in a weather resistant low loss fiberglass radome. The BA1010 ""Heavy Duty"" is permanently affixed to a unique mounting fixture which allows mounting on top of or along-side of most vertical supports. Due to their wide bandwidth, they are ideal for use as emergency backup antennas. Their size and mounting fixtures allow for easy storage and fast installation. Alternative mounting hardware is available for most applications.

FEATURES / BENEFITS

- Broadband reduces backup inventory and the need for multiple antennas.
- Fiberglass radome protects radiating elements in hostile environments.
- Copper elements maximize system performance while minimizing the possibility of intermod.



Technical features

	_						
		СТВ	$I \subset AI$	CDE		$C \wedge T$	IONS
CI	-61	LIK	ILAI	L SPE	CIF	CAI	IUIVO

Horizontal Pattern		OmniDirectional
Frequency Range	MHz	154 - 174
Horizontal Beamwidth	deg	N/A
Gain	dBi (dBd)	2.1
Vertical Beamwidth	deg	80
Polarization		Vertical
VSWR		< 1.5:1
Bandwidth for 1.5:1 VSWR	MHz	< 1.5:1
Impedance	Ohms	50
Maximum Power Input	W	500
Lightning Protection		Direct Ground
GENERAL SPECIFICATIONS		

Antenna Type Fiberglass Omni	
------------------------------	--

BA1010-2 REV : E amphenol-antennas.com

PRODUCT DATASHEET

BA1010-2





Connector Type		N Female
Connector Location		Bottom
Weight w/o Mtg Hardware	kg (lb)	4 (8.8)
Mount Type		Fixed
Mounting Hardware		Stainless Steel U-Bolts (E380-03F)
Rated Wind Speed	km/h (mph)	200 (125)
Flexible Extensions		None
Overall Length	m (ft)	1.4 (4.6)
Mounting Pipe Diameter	m (in)	0.08 (3)
Support Pipe Length	m (ft)	0.3 (1)
Radiating Element Material		Brass
Element Housing Material		Fiberglass
Radome Color		White RAL9010
Mounting Hardware Material		Stainless Steel U-Bolts (E380-03F)
Support Pipe Material		Black Powder Coated Aluminum
Max Wind Loading Area	m² (ft²)	0.08 (0.86)
Bend Mom @ Rated Wind 1" Below Top of Mt Pipe Comment		N/A
PACKAGING INFORMATION		
Shipping Weight	kg (lb)	5.9 (13)
Packing Dimensions, HxWxD	mm (in)	1650 x 110 x 110 (65 x 4.3 x 4.3)
Shipping Comment		N275F Mounting Bracket Packed w/antenna

External Document Links

Notes

• Radiating patterns: Request pattern files