

Feed through assemblies for 5/8" coaxial cable, 102mm (4"), 1-entry

4" Feed Through Boot Assembly 5/8" cable, 1-entry

## FEATURES / BENEFITS

These innovative boot assemblies feature a one-piece design which reduces installation time. The split, one-piece style simplifies clamping and frees the installers hands to position the cable runs. Boot assemblies are designed to be fitted onto 4"" entry panels in wall/roof feed-through applications. The durable boot is designed to met ASTM-D2000 and SAE J200 specifications. Each boot assembly includes the boot, two round member adapter clamps which fit inside the boot assembly to hold the coax in place.



Picture shows BOOT4-78-3 for illustration purpose

External Document Links	Notes
-------------------------	-------

## **Technical features**

STRUCTURE		
Product Line		Coaxial Cable Accessories
Product Type		Wall/Roof Feed-Through System
Feed-Through Component		Boot Assembly
Transmission Line Type		LCF58
Coaxial Cable Type		Foam Dielectric
Cable Size		5/8"
MECHANICAL SPECIFICATIONS		
Feed-Through Hole Diameter	mm (in)	102 (4)
Insert Holes		1
Mated to Cable Size and Interface		5/8
Color		Black
Material		EPDM rubber
TEMPERATURE SPECIFICATIONS		
Operation Temperature, °C°F)	°C(°F)	-50 to 85 (-58 to 185 )
Storage Temperature	°C(°F)	-50 to 85 (-58 to 185 )
PACKAGING INFORMATION		
Package Quantity		1
Weight per piece	kg (lb)	0.7 (1.54)
Box Dimensions (Bulk Shipping), L x W x H	mm (in)	635 x 330 x 178 (25 x 13 x 7)

BOOT4-58-1 REV : A REV DATE : 01 Dec 2008 www.rfstechnologies.com