

**BOOT4-78-3**

Feed through assemblies for 7/8" coaxial cable, 102mm (4"), 3-entries

## 4" Feed Through Boot Assembly 7/8" cable, 3-entries

**FEATURES / BENEFITS**

These innovative boot assemblies feature a one-piece design which reduces installation time. The split, one-piece style simplifies clamping and frees the installers hands to position the cable runs. Boot assemblies are designed to be fitted onto 4" entry panels in wall/roof feed-through applications. The durable boot is designed to meet ASTM-D2000 and SAE J200 specifications. Each boot assembly includes the boot, two round member adapter clamps which fit inside the boot assembly to hold the coax in place.



## External Document Links

## Notes

**Technical features****STRUCTURE**

Product Line		Coaxial Cable Accessories		
Product Type		Wall/Roof Feed-Through System		
Feed-Through Component		Boot Assembly		
Transmission Line Type		LCF78, UCF78		
Coaxial Cable Type		Foam Dielectric	Superflexible Foam Dielectric	Ultraflexible Foam Dielectric
Cable Size		7/8"		

**MECHANICAL SPECIFICATIONS**

Feed-Through Hole Diameter	mm (in)	102 (4)
Insert Holes		3
Mated to Cable Size and Interface		7/8
Color		Black
Material		EPDM rubber

**ACCESSORIES**

Spare Part / Useful Accessories		Cushion plug for unused hole : BOOT-CP-78
---------------------------------	--	---

**TEMPERATURE SPECIFICATIONS**

Operation Temperature, °C(°F)	°C(°F)	-50 to 85 (-58 to 185 )
Storage Temperature	°C(°F)	-50 to 85 (-58 to 185 )

**PACKAGING INFORMATION**

Package Quantity		1
Weight per piece	kg (lb)	0.7 (1.54)
Box Dimensions (Bulk Shipping), L x W x H	mm (in)	635 x 330 x 178 (25 x 13 x 7)