PRODUCT DATASHEET

BOOT4-78-3

Feed through assemblies for 7/8" coaxial cable, 102mm (4"), 3-entries

4" Feed Through Boot Assembly 7/8" cable, 3-entries

FEATURES / BENEFITS

These innovative boot assemblies feature a one-piece design which reduces installation time. The split, one-piece style simplifies clamping and frees the installers hands to position the cable runs. Boot assemblies are designed to be fitted onto 4"" entry panels in wall/roof feed-through applications. The durable boot is designed to met ASTM-D2000 and SAE J200 specifications. Each boot assembly includes the boot, two round member adapter clamps which fit inside the boot assembly to hold the coax in place.

External Document Links

Notes

Technical features

STRUCTURE

Product Line		Coaxial Cable Accessories		
Product Type		Wall/Roof Feed-Through System		
Feed-Through Component		Boot Assembly		
Transmission Line Type		LCF78, UCF78		
Coaxial Cable Type		Foam Dielectric	Superflexible Foam Dielectric	Ultraflexible Foam Dielectric
Cable Size		7/8"		

MECHANICAL SPECIFICATIONS

Feed-Through Hole Diameter	mm (in)	102 (4)
Insert Holes		3
Mated to Cable Size and Interface		7/8
Color		Black
Material		EPDM rubber

ACCESSORIES

Spare Part / Useful Accessories		Cushion plug for unused hole : BOOT-CP-78

TEMPERATURE SPECIFICATIONS

Operation Temperature, °C°F)	°C(°F)	-50 to 85 (-58 to 185)
Storage Temperature	°C(°F)	-50 to 85 (-58 to 185)

PACKAGING INFORMATION

Package Quantity		1
Weight per piece	kg (lb)	0.7 (1.54)
Box Dimensions (Bulk Shipping), L x W x H	mm (in)	635 x 330 x 178 (25 x 13 x 7)

All values nominal unless tolerances provided; information contained in the present datasheet is subject to confirmation at time of ordering