

**CLAMP-158**

Cable hanger, non-insulated, bolt-on, for 1 5/8" coaxial cable

Hanger, non-insulated, bolt-on for coaxial cable LCF158 and HCA158 and as fire resistance support for RCF158 and all RADIAFLEX® 1 5/8" with copper foil as outer conductor.

Made of stainless steel, kit of 10

FEATURES / BENEFITS

- Stainless steel hangers for supporting coaxial cable to tower.
 - Member mounting holes with up to M10 or 3/8"-16 hardware.
 - Hanger may be attached to angle adapters, tower standoffs.
 - Hanger may be attached to round member adapters through slot.
 - Installation every 10m (30ft) as fire resistance support for RADIAFLEX®. Keep's the RADIAFLEX® cable in position during fire impact to prevent potential blocking of escape path.
- All installation components should be made of stainless steel.

**External Document Links****Notes**

If using the Bolt-on hanger series in vertical runs, the hoisting grips need to be kept on the tower.

* Valid for all 1 5/8" types

Technical features**GENERAL SPECIFICATIONS**

Product Line		Coaxial Cable Accessories
Product Type		Hanger
Hanger Type		Bolt-On, non-insulated
Transmission Line Type		LCF158, HCA158, RCF158 RLF*, RLK*, RAY*, RLV*
Cable Type		Coaxial Foam Dielectric Air Dielectric

MECHANICAL SPECIFICATIONS

Cable Size		1-5/8
Number of Cable / Waveguide Runs		1
Material		Stainless Steel
Recommended / Maximum Clamp Spacing	m (ft)	0.8 / 1.2 (2.75 / 4)

TEMPERATURE SPECIFICATIONS

Operation Temperature	°C (°F)	-50 to 85 (-58 to 185)
Storage Temperature	°C (°F)	-50 to 85 (-58 to 185)

PACKAGING INFORMATION

Package Quantity		10
------------------	--	----