

FLEXWELL® Premium Elliptical Waveguide

FLEXWELL® elliptical waveguide is constructed of longitudinally continuous seam welded, highly conductive copper tube, corrugated and precision formed into an elliptical cross section. It is manufactured in continuous lengths using a special seam welding process developed by the RFS Technologies organization.

The corrugation design achieves high transverse stability, flexibility and crush strength for superior handling and forming at an installation. The inherent strength and flexibility of FLEXWELL® waveguide allows on location, a continuous length of waveguide to be run directly from a tower-mounted antenna to the equipment building.

A FLEXWELL® elliptical waveguide feeder requires less planning and reduces installation costs when compared to a feeder system using a rigid rectangular waveguide.

FLEXWELL® waveguide is available cut to length with factory attached connectors or in continuous lengths for termination in the field.

FEATURES / BENEFITS

- Designed for optimum system performance
- Excellent electrical performance
- Low loss and low VSWR (low return loss)
- Electrical test made on every waveguide during manufacturing
- Every waveguide passes pressure test
- Reduced installation cost and time compared to using rigid rectangular waveguides
- No need of flange joints, twist section and bends
- Easy transportation in coils or on drums
- Cutting at exact length and connectorizing in the field

Technical features

GENERAL SPECIFICATIONS

Performance	Standard (STD) or Premium (PREM) to be selected when ordering
Jacket	J (Polyethylene black) by default, JFN (Fire redartant black) upon request

ELECTRICAL SPECIFICATIONS

Typical Operating Band	GHz	10 - 11.7					
Max. VSWR / Return Loss	dB	1.062 / 30.5 Premium Performance (suggest to use with tunable or pre-tuned connectors to achieve optimal system performance) 1.15 / 23.1 Standard Performance					
Cut-off Frequency	GHz	6.49					

REV DATE: 18 Apr 2024



www.rfstechnologies.com

REV: B

EP105



FLEXWELL® Premium Elliptical Waveguide

Dimension over Jacket	mm (in)	33 x 20 (1.3 x 0.8)
Weight	kg/m (lb/ft)	0.5 (0.34)
Minimum Bending Radius E Plane, Single Bend	mm (in)	130 (5)
Minimum Bending Radius H Plane, Single Bend	mm (in)	280 (11)
Minimum Bending Radius E Plane, Repeated Bends	mm (in)	150 (6)
Minimum Bending Radius H Plane, Repeated Bends	mm (in)	300 (12)
Maximum Twist	degree/m (degree/ft)	6 (1.8)
Max. Operating Pressure	bar (psi)	0.5 (7)
Max. Pulling Length per Hoisting Grip	m (ft)	100 (305)
Standard Hanger Spacing	m (ft)	0.6 (2)
TEMPERATURE SPECIFICATIONS		
Installation Temperature	°C (°F)	-40 to 60 (-40 to 140)

Installation Temperature	°C (°F)	-40 to 60 (-40 to 140)
Storage Temperature	°C (°E)	-70 to 85 (.94 to 185.)

 Storage Temperature
 °C (°F)
 -70 to 85 (-94 to 185)

 Operation Temperature
 °C (°F)
 -50 to 85 (-58 to 185)

EP105REV : BREV DATE : 18 Apr 2024www.rfstechnologies.com



FLEXWELL® Premium Elliptical Waveguide

ATTENUATION AND POWER RATING

Frequency (GHz)	Attenuation dB/100m	Attenuation dB/100ft	Avarage Power (KW)	Group velocity (%c)	Group Delay (ns/100m)	Group Delay (ns/100ft)
10	9.58	2.92	1.69	76.1	438.4	133.6
10.1	9.51	2.90	1.70	76.6	435.3	132.7
10.2	9.45	2.88	1.71	77.1	432.4	131.8
10.3	9.40	2.86	1.72	77.7	429.6	130.9
10.4	9.34	2.85	1.73	78.1	426.9	130.1
10.5	9.29	2.83	1.74	78.6	424.3	129.3
10.6	9.25	2.82	1.75	79.1	421.9	128.6
10.7	9.20	2.81	1.76	79.5	419.6	127.9
10.8	9.16	2.79	1.77	79.9	417.3	127.2
10.9	9.13	2.78	1.78	80.3	415.2	126.5
11	9.09	2.77	1.78	80.7	413.1	125.9
11.1	9.06	2.76	1.79	81.1	411.2	125.3
11.2	9.03	2.75	1.79	81.5	409.3	124.7
11.3	9	2.74	1.80	81.9	407.5	124.2
11.4	8.97	2.73	1.81	82.2	405.7	123.7
11.5	8.94	2.73	1.81	82.6	404.1	123.2
11.6	8.92	2.72	1.82	82.9	402.4	122.7
11.7	8.90	2.71	1.82	83.2	400.9	122.2

External Document Links

Notes

Recommend premium performance waveguides to be used with tunable or pre-tuned connectors.

VSWR values include connectors and are valid for frequency band of connectors.

Max. Operating Band: 8.10 - 11.70 GHz

EP105REV : BREV DATE : 18 Apr 2024www.rfstechnologies.com