

Discontinuing product **GKIT-60-060**

Grounding Kit, Pre-formed Copper Strap, for E60

The grounding kit with pre-formed copper strap facilitates installation with a pre-formed copper strap that eliminates the need for a coiling tool. This kit has been verified by independent labs to protect coax from the damaging effects of lightning currents.

FEATURES / BENEFITS

The Standard Grounding Kit is designed to comply with RoHS (EU 2002/95/EC) and CRoHS (China SJ/T11363-2006) directives and has been verified by independent labs to withstand the damaging effects of lightning current. The pre-formed copper strap and associated hardware facilitates a proper attachment to the elliptical waveguide, insuring that the performance of the elliptical waveguide is not being compromised. The 6-gauge, 7 strand copper wire provides the most practical and effective low-inductance transfer of lightning induced current from your elliptical waveguide to your system ground.



Technical features

CT	-	107		-	-
21	κι	JCI	ΙU	к	E

Product Line	Elliptical Waveguide Accessories
Type of Grounding Kit	Pre-Formed Copper Strap
Transmission Line Type	E60, EP60
Cable Type	Elliptical Waveguide
Cable Size	E60

MECHANICAL SPECIFICATIONS

Lug Attachment Method		Field Attachable		
Lug Style Size		2-hole Ø 9.5mm (3/8") crimp-on, tin-plated		
Grounding Wire Length	m (in)	1.5 (60)		
Grounding Wire Size	mm²	6 AWG (7 strand)		
Grounding Wire Color		Black		
Grounding Body Color		Black		
Sealing Class		IP68		

PACKAGING INFORMATION

Package Quantity		1	

External Document Links

Notes

Discontinuing product GKIT-60-060

REV: E

REV DATE: 01 Jun 2014

www.rfstechnologies.com