

**KRTS2-E**

Tower Stand-off Kit 127-152mm (5-6") Diameter, 3/8" Hardware

Stainless steel standoff adapter with 3/8" thread  
Stainless steel round member adapter 127-152mm (4-6in)

**FEATURES / BENEFITS**

- Constructed of heavy stainless steel
- The stand-offs provide 1-1/4" (30 mm) tower clearance to hangers when running waveguide over tower cross members, flanges and other tower obstacles.
- The kit consists of ten stainless steel tower stand-offs with stainless steel hardware.
- Use with Threaded Rod Kit for additional tower clearance.



Stand-off Kit KRTS2-E

**Technical features****STRUCTURE**

|                            |  |   |                 |
|----------------------------|--|---|-----------------|
| Product Line               |  | Elliptical Waveguide Accessories<br>Coaxial Cable Accessories |                 |
| Product Type               |  | Installation Hardware   |                 |
| Installation Hardware Type |  | Round Member Tower Stand-off Kit                              |                 |
| Coaxial Cable Type         |  | Air Dielectric  | Foam Dielectric |
| Configuration              |  | 127-152mm (5-6") Diameter, 3/8" Hardware                      |                 |

**MECHANICAL SPECIFICATIONS**

|                       |         |                    |
|-----------------------|---------|--------------------|
| Tower Member Diameter | mm (in) | 127 - 152 (5 - 6 ) |
| Material              |         | Stainless Steel    |

**TEMPERATURE SPECIFICATIONS**

|                          |         |                         |
|--------------------------|---------|-------------------------|
| Installation Temperature | °C (°F) | -50 to 85 (-58 to 185 ) |
| Operation Temperature    | °C (°F) | -50 to 85 (-58 to 185 ) |
| Storage Temperature      | °C (°F) | -50 to 85 (-58 to 185 ) |

**PACKAGING INFORMATION**

|                  |  |    |
|------------------|--|----|
| Package Quantity |  | 10 |
|------------------|--|----|

[External Document Links](#)[Notes](#)