

Single-block hanger with three layer, with angle member adapter

Single block hanger support systems are designed for organizing bundled runs of coax cable and trunk cable.

Each space-saving block securely holds two runs of cables, allowing a compact bundle of up to 3x runs to be supported by stacking three blocks.

FEATURES / BENEFITS

Multi Blocks are manufactured of polypropylene providing thermal, chemical and UV resistance in all environments.

They come including angle member adapter and necessary hardware.

The angle member adapter fastens the clamp to the tower without drilling.

The angle member adapter includes a tower member set screw.

The hanger mounting rod may be located in either of two mounting holes, depending on orientation of the fixing member.

Compliant to RoHS (EU 2002/95/EC) and CRoHS (China SJ/T11363-2006) i.e. usable on a global basis.



External Document Links Notes

Technical features

GENERAL SPECIFICATIONS

Product Line	Hybrid Cable Accessories
Product Type	Hanger
Hanger Type	Single-block
Transmission Line Type	F/O cable fixation LCF12 clamp with rubber inlet
Color	Black

MECHANICAL SPECIFICATIONS					
Cable Size	1/2				
Number of Cable / Waveguide Runs		3 layers, 3 runs			
Configuration		Incl. Angle member adapter			
Material		Metal parts: -Connecting devices:Stainless steel -Angle member adapter: Stainless steel -Plastic parts: Polypropylene			
Length	mm (in)	162 (6.38)			
Height	mm (in)	50 (1.96)			
Width	mm (in)	50 (1.96)			
Recommended / Maximum Clamp Spacing	m (ft)	1 / 1.2 (3.25 / 4)			
TEMPERATURE SPECIFICATIONS					

Operation Temperature	°C (°F)	-40 to 85 (-58 to 185)
Storage Temperature	°C (°F)	-40 to 85 (-58 to 185)
DACKAGING INFORMATION		

Weight per piece	kg (lb)	0.18 ((0.4))

www.rfstechnologies.com MBHT07-3-F REV: A REV DATE: 07 May 2020