




N-Adapter to PDR140, female gasket and screw kit enclosure


**FEATURES / BENEFITS**

Waveguide installation

- The rectangular waveguide component provides simple installation in particular difficult cases
- The flange adapter provides proper matching of rectangular waveguide flanges to N-female connector
- It provides outstanding electrical performance



PDR



Coax transition for R120 and smaller waveguides

**Technical features**

**STRUCTURE**

|   |  |   |
|---|--|---|
| Type of Rectangular Waveguide Component |  | Waveguide to Type N Female Coax Adapter |
| Waveguide Size IEC (EIA)                |  | R140 (WR62)                             |
| Coaxial Interface                       |  | N-female                                |
| Flange                                  |  | PDR140                                  |
| Flange Finish                           |  | Brass un-plated                         |

**ELECTRICAL SPECIFICATIONS**

|                                 |           |             |
|---------------------------------|-----------|-------------|
| Frequency Range                 | GHz       | 11.9 - 18   |
| Minimum Return Loss (max. VSWR) | dB (VSWR) | 19.1 (1.25) |

**MATERIAL**

|          |  |       |
|----------|--|-------|
| Material |  | Brass |
| Color    |  | Black |

**PACKAGING INFORMATION**

|                  |  |   |
|------------------|--|---|
| Package Quantity |  | 1 |
|------------------|--|---|

[External Document Links](#)

[Notes](#)