PRODUCT DATASHEET

NF-LCF12-C02-6

N Female Connector for 1/2" Coaxial Cable, OMNI FIT™ standard, extended frequency range

OMNI FIT™ high performance connectors are designed for use with both CELLFLEX® (copper) and CELLFLEX® Lite (aluminum) cables. They are designed specifically to provide the highest quality connector-cable interface while simplifying and speeding up connector attachment. All RFS Technologies connectors are fully tested for mechanical and electrical compliance to industry specifications.



OMNI FIT™ Standard Connectors

FEATURES / BENEFITS

- Cost effective two-piece design for safe and easy installation
- Compatible with copper and aluminium cable types i.e. one connector for both outer conductor materials eliminates the risk of faulty connector installation and helps to keep inventory down
- Robust mechanical design for low and consistent intermodulation performance i.e. keeps the mobile network performance up reduces the number of dropped calls and avoids revenue losses
- Superior electrical performance for consistent and repeatable VSWR i.e. ensure network system performance
- Waterproof to IP 68 i.e. no downtime risk, secures revenue
- RoHS (EU) and CRoHS (China) compliant i.e. can be used on a global basis

Technical features

GENERAL SPECIFICATIONS

Transmission Line Type		Coaxial Cable	
Cable Size		1/2	
Cable Type		Foam Dielectric	Radiating
Model Series		LCF12-50 Series	ICA12-50 Series
Connector Interface		N	
Connector Type		OMNI FIT™ Standard	
Sealing Method		O-ring	
Gender		Female	

ELECTRICAL SPECIFICATIONS

Nominal Impedance, ohms	Ohm	50
3rd Order IM Product @ 2x20 Watts	dBc	-159 typical
Maximum Frequency	GHz	6
VSWR, Return Loss	VSWR (dB)	0 < f ≤ 1.0 GHz: 1.03 (36.6) 1.0 < f ≤ 2.7 GHz: 1.04 (34.1) 2.7 < f ≤ 3.7 GHz: 1.08 (28.3) 3.7 < f ≤ 6.0 GHz: 1.08 (28)

MECHANICAL SPECIFICATIONS

Plating Outer/Inner		Trimetal/Silver
Length	mm (in)	55.4 (2.18)
Outer Diameter	mm (in)	25.9 (1)
Inner Contact Attachment		Basket
Outer Contact Attachment		Spring C-Ring

All values nominal unless tolerances provided; information contained in the present datasheet is subject to confirmation at time of ordering

NF-LCF12-C02-6


N Female Connector for 1/2" Coaxial Cable, OMNI FIT™ standard, extended frequency range

ACCESSORIES

Wrench size front	mm (in)	24 (15/16)
Wrench size rear	mm (in)	24 (15/16)

TESTING AND ENVIRONMENTAL

Waterproof Level		IP68



External Document Links

Application Note

Installation instruction

Notes

All values nominal unless tolerances provided; information contained in the present datasheet is subject to confirmation at time of ordering