



Coaxial Adapter N female - female

## FEATURES / BENEFITS



## External Document Links

## Notes

## Technical features

## STRUCTURE

Product Line		Coaxial Cable Components
Product Type		Coaxial Adapter

## MECHANICAL SPECIFICATIONS

Connector A		N Female
Center Contact Connector A		Phosphor Bronze, silver plated
Outer Contact Connector A		Brass, Tri metal alloy plated
Connector B		N Female
Center Contact Connector B		Phosphor Bronze, silver plated
Outer Contact Connector B		Brass, Tri metal alloy plated
Dielectric		PTFE
Sealing class		IP68, connected

## ELECTRICAL SPECIFICATIONS

Frequency Range - MHz		DC - 6000
VSWR, Return Loss	VSWR (dB)	0-2000 MHz: 1.04 (34.15) 2000-3000 MHz: 1.06 (30.71) 3000-6000 MHz: 1.10 (26.44)
Insertion Loss, dB (Max)	dB	0.05
3rd Order IM Product @ 2x20 Watts	dBc	< -163

## TEMPERATURE SPECIFICATIONS

Operation Temperature	°C (°F)	-45 to 85 (-49 to 185)
-----------------------	---------	------------------------

## PACKAGING INFORMATION

Package Quantity		1
------------------	--	---