

N Male Connector for 1/2" Coaxial Cable, OMNI FIT™ standard, O-ring sealing

OMNI FITTM high performance connectors are designed for use with both CELLFLEX® (copper) and CELLFLEX® Lite (aluminum) cables. They are designed specifically to provide the highest quality connector-cable interface while simplifying and speeding up connector attachment.

FEATURES / BENEFITS

- Cost effective two-piece design for safe and easy installation
- Compatible with copper and aluminium cable types i.e. one connector for both outer conductor materials eliminates the risk of faulty connector installation and helps to keep inventory down
- Robust mechanical design for low and consistent intermodulation performance i.e. keeps the mobile network performance up reduces the number of dropped calls and avoids revenue losses
- Superior electrical performance for consistent and repeatable VSWR i.e. ensure network system performance
- Waterproof to IP 68 i.e. no downtime risk, secures revenue
- RoHS (EU) and CRoHS (China) compliant i.e. can be used on a global basis



NM-LCF12-C03

Technical features

GENERAL SPECIFICATIONS

Transmission Line Type		Coaxial Cable		
Cable Size		1/2		
Model Series	LCF12-50 Series	ICA12-50 Series	RCF12-50 Series	RCA12-50 Series
Connector Interface		N		
Connector Type		OMNI FIT	™ Standard	
Sealing Method		O-ring		
Gender		Male		

ELECTRICAL SPECIFICATIONS

Nominal Impedance, ohms	Ohm	50
3rd Order IM Product @ 2x20 Watts	dBc	-157 ; typical -160
Maximum Frequency	GHz	6.0
VSWR, Return Loss	VSWR (dB)	0 < $f \le 1.0$ GHz: 1.03 (36.6) 1.0 < $f \le 2.7$ GHz: 1.04 (34.1) 2.7 < $f \le 3.7$ GHz: 1.08 (28.3) 3.7 < $f \le 5.0$ GHz: 1.15 (23.1) 5.0 < $f \le 6.0$ GHz: 1.25 (19.1)

MECHANICAL SPECIFICATIONS

Plating Outer/Inner		Trimetal/Silver
Length	mm (in)	56.5 (2.23)
Outer Diameter	mm (in)	22 (0.87)
Inner Contact Attachment		Spring Finger
Outer Contact Attachment		Spring C-Ring

NM-LCF12-C03 REV : D REV DATE : 14 Oct 2025 www.rfstechnologies.com




N Male Connector for 1/2" Coaxial Cable, OMNI FIT™ standard, O-ring sealing

ACCESSORIES

Wrench size front	mm (in)	20 (13/16)
Wrench size rear	mm (in)	20 (13/16)
Trimming Tool		TRIM-SET-L12-C02

TESTING AND ENVIRONMENTAL

Waterproof Level IP68



NM-LCF12-C03 Outline Drawing

External Document Links Installation Instruction Notes

NM-LCF12-C03 REV : D REV DATE : 14 Oct 2025 www.rfstechnologies.com