



OMNI FIT™ high performance connectors are designed for use with both CELLFLEX® (copper) and CELLFLEX® Lite (aluminium) cables. They are designed specifically to provide the highest quality connector-cable interface while simplifying and speeding up connector attachment. All RFS connectors are fully tested for mechanical and electrical compliance to industry specifications. The N connector meets all technical requirements and covers high frequencies as well as legacy applications. Sealing against outer conductor and jacket by means of o-ring and 360° compression fit.

#### FEATURES / BENEFITS

- Ultra high PIM performance i.e. reduced interference leading to high customer satisfaction
- Two-piece design i.e. visual inspection of interlocking leads to improved installation security
- OMNI FIT™ concept i.e. streamlined order management and reduced stock level
- Watertight sealing in mated and unmated condition, i.e. reduced efforts during installation and improved security during operation
- Tri metal alloy plating i.e. extreme resistance against corrosion even under hardest climatic and environmental circumstances
- Multi-thread (Tristart) design i.e. simplified and accelerated tightening process
- RoHS (EU) and CRoHS (China) compliant i.e. can be used on a global basis



RAPIT FIT™ Connectors

[External Document Links](#)[Notes](#)[Installation Instruction](#)

## Technical features

#### GENERAL SPECIFICATIONS

Transmission Line Type		Coaxial Cable
Cable Size		3/8
Cable Type		Foam Dielectric
Connector Interface		N
Connector Type		OMNI FIT™ PREMIUM Straight
Sealing Method		O-ring + 360° Compression
Gender		Male

#### ELECTRICAL SPECIFICATIONS

Nominal Impedance, ohms	Ohm	50
3rd Order IM Product @ 2x20 Watts	dBc	-163 ; typical -167
Maximum Frequency	GHz	6
VSWR, Return Loss	VSWR (dB)	0 &lt; f ≤ 1.0 GHz: 1.02 (40) 1.0 &lt; f ≤ 2.2 GHz: 1.03 (37) 2.2 &lt; f ≤ 2.7 GHz: 1.03 (37) 2.7 &lt; f ≤ 3.8 GHz: 1.08 (28) 3.8 &lt; f ≤ 5.0 GHz: 1.15 (23) 5.0 &lt; f ≤ 6.0 GHz: 1.22 (20)

**NM-LCF38-E01**

N Male Straight Connector for 3/8" Coaxial Cable, OMNI FIT™ Premium

**MECHANICAL SPECIFICATIONS**

Plating Outer/Inner		Tri metal alloy/Silver
Length	mm (in)	65 (2.559)
Outer Diameter	mm (in)	24 (0.945)
Inner Contact Attachment		Basket
Outer Contact Attachment		Spring Finger

**ACCESSORIES**

Wrench size front	mm (in)	22 (19)
Wrench size rear	mm (in)	22

**TESTING AND ENVIRONMENTAL**

Waterproof Level		IP68
------------------	--	------

