



OMNI FIT™ high performance connectors are designed for use with both CELLFLEX® (copper) and CELLFLEX® Lite (aluminum) cables. They are designed specifically to provide the highest quality connector-cable interface while simplifying and speeding up connector attachment. All RFS connectors are fully tested for mechanical and electrical compliance to industry specifications.

#### FEATURES / BENEFITS

- Cost effective two-piece design for safe and easy installation
- Compatible with copper and aluminium cable types i.e. one connector for both outer conductor materials eliminates the risk of faulty connector installation and helps to keep inventory down
- Robust mechanical design for low and consistent intermodulation performance i.e. keeps the mobile network performance up reduces the number of dropped calls and avoids revenue losses
- Superior electrical performance for consistent and repeatable VSWR i.e. ensure network system performance
- Waterproof to IP 68 i.e. no downtime risk, secures revenue
- RoHS (EU) and CRoHS (China) compliant i.e. can be used on a global basis

NO IMAGE  
AVAILABLE

[External Document Links](#)[Notes](#)[Application Note](#)[Installation instruction](#)

## Technical features

### GENERAL SPECIFICATIONS

Transmission Line Type		Coaxial Cable		
Cable Size		1/2		
Cable Type		Foam Dielectric		Radiating
Model Series		LCF12-50 Series	ICA12-50 Series	RCF12-50 Series
Connector Interface		N		
Connector Type		OMNI FIT™ Standard Right Angle		
Sealing Method		O-ring		
Gender		Male		

### ELECTRICAL SPECIFICATIONS

Nominal Impedance, ohms	Ohm	50
3rd Order IM Product @ 2x20 Watts	dBc	-159 typical
Maximum Frequency	GHz	6
VSWR, Return Loss	VSWR (dB)	0 &lt; f ≤ 1.0 GHz: 1.04 (34.2) 1.0 &lt; f ≤ 2.0 GHz: 1.06 (30.7) 2.0 &lt; f ≤ 2.7 GHz: 1.10 (26.4) 2.7 &lt; f ≤ 3.7 GHz: 1.12 (24.9) 3.7 &lt; f ≤ 6.0 GHz: 1.15 (23.1)

### MECHANICAL SPECIFICATIONS

Plating Outer/Inner		Trimetal/Silver
Length	mm (in)	52.3 (2.06)
Outer Diameter	mm (in)	49.5 (1.95)
Inner Contact Attachment		Basket
Outer Contact Attachment		Spring C-Ring

**NMR-LCF12-C02**

N Male Right Angle Connector for 1/2" Coaxial Cable, OMNI FIT™ standard

**ACCESSORIES**

<b>Wrench size front</b>	mm (in)	24 (15/16)
<b>Wrench size rear</b>	mm (in)	24 (15/16)

**TESTING AND ENVIRONMENTAL**

<b>Waterproof Level</b>		IP68
-------------------------	--	------