




This PDS*DE series are Power Splitters, designed to evenly split high power cellular signals with minimal reflections or loss. They are specified to cover 380- 2700 MHz.

The wide frequency range allows to use these splitters for multiband wireless Distributed Antenna Systems (DAS) or in combination with RADIAFLEX® radiating cable products. With few solder joints and an air dielectric, the loss is minimal and reliability enhanced.

Image not found or type unknown



PDS2DE-380/2700-01

FEATURES / BENEFITS

- Multiple-Band Frequency Ranges
- 500 Watt Power Rating
- High Reliability
- Low Cost Design for ease of mounting
- 7-16 DIN-female Connectors

Technical features

STRUCTURE

Product Type		Power Divider
Techn. Application		Indoor
Number of Input Ports		1
Number of Output Ports		2
Connectors		7-16 female

ELECTRICAL SPECIFICATIONS

Frequency Range	MHz	380 - 2700
Impedance	Ohm	50
Max. Insertion Loss	dB	3.4
Max. VSWR / Return Loss, dB	VSWR/dB	1.3 / 17.7
Intermodulation (IM3)		-150 dBc with 2x43 dBm tones
Total Input Power	W	500
RF Peak Power	kW	1000

TEMPERATURE SPECIFICATIONS

Temperature Range	°C (°F)	-25 to +65 (-13 to +149)
-------------------	---------	--------------------------

MECHANICAL SPECIFICATIONS

Height (Less Connectors)	mm (in)	43.1 (1.7)
Width (Less Connectors)	mm (in)	47.5 (1.87)
Length (Less Connectors)	mm (in)	281.1 (11.07)

TESTING AND ENVIRONMENTAL

Environmental Class		IP65
---------------------	--	------

Dimensions in mm

External Document Links

Notes