



- RADIAFLEX® series functions as a distributed antenna to provide communications in tunnels, mines and large building complexes and is the solution for any application in confined areas.
- Slots in the copper outer conductor allow a controlled portion of the internal RF energy to be radiated into the surrounding environment. Conversely, a signal transmitted near the cable will couple into the slots and be carried along the cable length.
- RADIAFLEX® is used for both one-way and two-way communication systems and because of its broadband capability, a single radiating waveguide can handle multiple communication systems simultaneously.
- This RADIAFLEX® radiating waveguide is constructed of longitudinally continuous seam welded, highly conductive copper tube, corrugated and precision formed into an elliptical cross section. It is manufactured in continuous lengths using a special seam welding process developed by the RFS organization. The product offers a superior electrical performance together with good bending properties.

FEATURES / BENEFITS

- Optimized for ultra high frequency applications from 5 GHz to 6 GHz
- Best-in-class, RF wideband radiating waveguide with technology agnostic performance
- Designed for a variety of in-tunnel applications
- Lowest insertion loss and excellent coupling performance to minimize count of active equipment; low coupling loss variations
- Maintains functionality even in case of a fire



RE elliptical waveguide

Technical features

GENERAL SPECIFICATIONS

Size		RE60
------	--	------

ELECTRICAL SPECIFICATIONS

Max. Operating Frequency	MHz	6000
Cable Type		RE
Frequency Selection	MHz	6000

**MECHANICAL SPECIFICATIONS**

Jacket Description		Halogen free, non corrosive, flame and fire retardant, low smoke, polyolefin
Slot Design		Milled
Outer Conductor Material		Corrugated Copper Tube
Dimension over Jacket	mm (in)	56 x 33 (2.2 x 1.3)
Min. Bending Radius E Plane w/o rebending	mm (in)	200 (8)
Min. Bending Radius H Plane w/o rebending	mm (in)	550 (22)
Min. Bending Radius E Plane with rebending	mm (in)	300 (12)
Min. Bending Radius H Plane with rebending	mm (in)	800 (31)
Cable Weight	kg/m (lb/ft)	1.1 (0.74)
Indication of Slot Alignment		Printing on jacket
Recommended / Maximum Clamp Spacing	m (ft)	2 (5)
Minimum Distance to Wall	mm (in)	50 (2)

TESTING AND ENVIRONMENTAL

Jacket Testing Methods		Test methods for fire behaviour of cable : IEC 60754-1/-2 smoke emission: halogen free, non corrosive IEC 61034 low smoke IEC 60332-1 flame retardant IEC 60332-3-24 fire retardant
------------------------	--	---

TEMPERATURE SPECIFICATIONS

Storage Temperature	°C(°F)	-70 to 85 (-94 to 185)
Installation Temperature	°C(°F)	-25 to 60 (-13 to 140)
Operation Temperature	°C(°F)	-40 to 85 (-40 to 185)

ATTENUATION AND POWER RATING

Frequency, MHz	Longitudinal Loss, dB/100 m (dB/100 ft)	Coupling Loss 50%, dB	Coupling Loss 95%, dB
5000	4.90 (1.49)	74	80
5100	4.90 (1.49)	74	80
5200	4.80 (1.46)	74	80
5300	4.80 (1.46)	74	80
5400	4.80 (1.46)	74	80
5500	4.80 (1.46)	74	80
5600	4.80 (1.46)	74	80
5700	4.80 (1.46)	74	80
5800	4.80 (1.46)	74	80
5900	4.80 (1.46)	74	80
6000	4.80 (1.46)	74	80



External Document Links

Notes

- Coupling loss as well as longitudinal attenuation of RADIAFLEX® elliptical waveguides is measured by the free space method according to IEC 61196-4.
- Coupling loss values are measured with a log-periodic antenna with gain of approx. 6 dBi in specified frequency range.
- The coupling loss values are average values of the three spatial orientations (radial, parallel and orthogonal) of log-periodic antenna.
- Coupling loss values are given with a tolerance of ± 6 dB and longitudinal loss values with a tolerance of $\pm 5\%$.
- As with any radiating element, the performance in building or tunnel environments may deviate from figures based on free space method.