



The RSB Clip RSB-78 is designed for the installation of CELLFLEX® foam-dielectric cables of 7/8" size. The clip is a universal clamp device and can be used in many mounting configurations. When replacing a cable the clip can be opened without any tools. After replacing the cable the clips are easily closed again. The RSB is the abbreviation of Rostfreier Stahlbügel and means stainless steel hanger. The hanger is resistant against all environmental influences. Due to its mechanical construction cable deformation is impossible and deterioration of the electrical properties is avoided.

FEATURES / BENEFITS

[External Document Links](#)[Notes](#)[Application Note RSB Clip](#)[Installation Instruction](#)

Technical features

GENERAL SPECIFICATIONS

Product Line		Coaxial Cable Accessories Hybrid Cable Accessories
Product Type		Hanger
Hanger Type		RSB-Clip
Transmission Line Type		LCF78 UCF78 RLF78, RLFW78 RAY78, RAYB78 RLKU78 RLKW78 RCF78 HB078 HCA78
Cable Type		Coaxial Foam Dielectric Air Dielectric

MECHANICAL SPECIFICATIONS

Cable Size		7/8
Number of Cable / Waveguide Runs		1
Material		Stainless Steel
Drill Hole Size	mm (in)	8 (0.315)

ACCESSORIES

Spare Part / Useful Accessories		Cleat : RSB-310 Anchor bar fixation : RSB-315
---------------------------------	--	--

TEMPERATURE SPECIFICATIONS

Installation Temperature	°C (°F)	-50 to 85 (-58 to 185)
Operation Temperature	°C (°F)	-50 to 85 (-58 to 185)
Storage Temperature	°C (°F)	-50 to 85 (-58 to 185)



PACKAGING INFORMATION

Package Quantity		10
------------------	--	----