

Screw M8 x 90 mm (3.55 in) for metal plug

The screw fixes the HDC clamp to the wall.

FEATURES / BENEFITS

Stainless steel, A4, for HDC clamp



## **Technical features**

				_	_
ST	ווס	$\boldsymbol{c}$		D	-
31	NU	<b>C</b> I	v	ıv	_

Product Line	Radiating Cable Accessories	
Product Type	Installation Hardware	
Installation Hardware Type	Screw	
Transmission Line Type	RADIAFLEX®cable with copper foil as outer conductor, cable size 114 and 158	
Coaxial Cable Type	Radiating Cable	
Cable Size	1-1/4"	1-5/8"
Configuration	Screw for HDC clamp	

## **MECHANICAL SPECIFICATIONS**

Angle member adpter threads		M8	
Material		Stainless Steel, A4	
Thread	mm (in)	M8	
Length	mm (in)	90 (3.55)	

## **TEMPERATURE SPECIFICATIONS**

Installation Temperature	°C (°F)	-50 to 85 (-58 to 185 )
Operation Temperature	°C (°F)	-50 to 85 (-58 to 185 )
Storage Temperature	°C (°F)	-50 to 85 (-58 to 185 )

## **PACKAGING INFORMATION**

Package Quantity	100
rackage Qualitity	100

**External Document Links** 

Notes

S-890-2 REV : A REV DATE : 06 Sep 2012 **www.rfstechnologies.com**