# Broadband Low PIM Load for Wireless & Indoor Application, Support 350-6000MHz, 200W

## PRODUCT DESCRIPTION

RFS Technologies TERP-E series Low PIM Loads have been designed for a variety of wireless applications in the frequency band from 350 to 6000MHz with excellent PIM value. The products are ideally suited for termination of unused ports in distributed antenna systems or in RADIAFLEX® radiating cables systems. The loads feature an outstanding PIM performance to avoid interferences in 3G / 4G / 5G communication systems.

## **FEATURES / BENEFITS**

- · Broadband 350MHz-6000MHz
- N Male Interface
- PIM Optimized Design (163dBc @2x43dBm)
- Low VSWR



## **TECHNICAL FEATURES**

#### **ELECTRICAL SPECIFICATIONS**

Frequency Range	MHz	350-6000		
VSWR		1.22:1@350-2700MHz, 1.3:1@2701-6000MHz		
PIM 3rd @2*43 dBm	dBc	163		
Input Impedance	Ohm	50		

#### **MECHANICAL SPECIFICATIONS**

Connectors		N Male
Temperature Range	°C	-25 to +50
IP Level		IP65
RoHS		Compliant

## **MODEL NUMBER SPECIFICATIONS**

Model Number		TERP-E-6000-2W	TERP-E-6000-5W	TERP-E-6000-10W	TERP-E-6000-20W
Average Power	Watts	2	5	10	20
Dimensions, L*W*H	mm (in)	50*77 (1.97*3.03)	50*97 (1.97*3.82)	44*141 (1.73*5.55)	54*169 (2.13*6.65)
Net Weight ±10%	kg(lb)	0.255(0.56)	0.41(0.9)	0.525(1.16)	0.725(1.6)

#### **MODEL NUMBER SPECIFICATIONS**

Model Number		TERP-E-6000-50W	TERP-E-6000-100W	TERP-E-6000-200W
Average Power	Watts	50	100	200
Dimensions, L*W*H	mm (in)	173*60*74 (6.81*2.36*2.91)	233*130*75 (9.17*5.12*2.95)	233*130*126 (9.17*5.12*4.96)
Net Weight ±10%	kg(lb)	1.255(2.77)	2.32(5.11)	4.19(9.24)

TERP-E-6000-200W REV : P2 REV DATE : 04 Aug 2021 www.rfstechnologies.com



Broadband Low PIM Load for Wireless & Indoor Application, Support 350-6000MHz, 200W

External Document Links	Notes
LINK to VEX FILES	

TERP-E-6000-200W REV : P2 REV DATE : 04 Aug 2021 www.rfstechnologies.com