




RFS Technologies TPS\* Tapper product family has been designed to support a variety of wireless applications in the frequency band from 694 to 3800MHz. The units couple off a defined fraction of a RF signal from typically 3 to 30 dB with minimal reflections or loss. The broad frequency range is ideally suited for 3G / 4G / 5G multi-band distributed antenna systems or in combination with RADIAFLEX® radiating cables. Notably, these products feature a low level of network interferences due to their PIM optimized desing.

#### FEATURES / BENEFITS

- Split ratio 30:1 / 15dB
- 4.3-10-female interfaces
- PIM optimized design ( $\leq 160$  @2x +43dBm)
- Low insertion loss
- High power handling
- Small size, Low weight



TPS15-43-694/3800 (similar product illustration)

## Technical features

#### STRUCTURE

Product Type		Unequal Power Divider/Tapper
Techn. Application		Indoor
Number of Input Ports		1
Number of Output Ports		2

#### ELECTRICAL SPECIFICATIONS

Frequency Range	MHz	694 - 3800
Connector Type		4.3-10 Female
Max. VSWR / Return Loss	VSWR/dB	1.30/17.7 (1.3)
Insertion Loss max.	dB	0.2
Coupling Value	dB	15
Coupling Flatness max.	dB	+2.0 / -2.0
Intermodulation (IM3)		$\leq 160$ dBc (2x +43dBm)
Impedance	Ohm	50
Total Input Power	W	200

#### TEMPERATURE SPECIFICATIONS

Temperature Range	°C (°F)	-25 to +65 (-13 to +149)
-------------------	---------	--------------------------

#### MECHANICAL SPECIFICATIONS

Height	mm (in)	51.1 (2.01)
Width	mm (in)	19.5 (0.77)
Length	mm (in)	99.3 (3.91)


#### TESTING AND ENVIRONMENTAL

Environmental Class		IP65
---------------------	--	------



## TPS15-43-694/3800

Unequal Power Divider/Tapper, 15dB / 30:1, 694-3800MHz, 4.3-10 Female, IP65



Outline Drawing

### External Document Links

### Notes