PRODUCT DATASHEET

TRIM-SET-R12-P02

Combination preparation tool (Universal Trimming Tool), RADIAFLEX® Cable 1/2" for P-Series connector

The trimming tool improves the cable preparation prior to connector attachment. No further tools are required to prepare the cable for the connector attachment. Due to the unique design of the trimming tool, it combines all necessary functions in one tool. It can be used for all RADIAFLEX® 1/2'' cables in combination with the RADIAFLEX® P-Series connector.

The Universal Trimming Tools Series offers the additional advantage to be convertible to different cable sizes (1/4"", 3/8"", 1/2"" and 7/8"") only by changing the insert. Different inserts are available as optional items, for references see below or contact your RFS Technologies sales contact.



only for illustration TRIM-SET-R78-P02

FEATURES / BENEFITS

- **Universal Trimming Tool concept**
  One basic tool can be used for cables sizes 1/4"", 3/8"", 1/2"" and 7/8"" only by changing the insert
- **Precision cable preparation tool**
  Always exact and repeatable trimming dimensions
- **Intuitive use of tool**
  Easy and precise preparation of cables for connector installation
- **Long-lasting cutting blades**
  Easy to clean, smooth dielectric surface improves IM performance

Technical features

STRUCTURE		
Product Line		Coaxial Cable Accessories
Product Type		Tool
Transmission Line Type		RADIAFLEX radiating cables of RLK, RAY, RLF series
Coaxial Cable Type		Foam dielectric radiating cables with copper foil outer conductor
Cable Size		1/2"
Type of Tool		Combination Cable Preparation Tool
Configuration		Universal Trimming Tool
ACCESSORIES		
Spare Part / Useful Accessories		Spare blades : TRIM-B30
MECHANICAL SPECIFICATIONS		
Color		Red
Material		Fiberglass reinforced Polycarbonate
PACKAGING INFORMATION		
Package Quantity		1
Weight per piece	kg (lb)	0.19 (0.42)

External Document Links

Notes

Available inserts to convert every red tool for use with RADIAFLEX® 1/2"" cable series and P02 connector family:

- TRIM-IR12-P02
- TRIM-FR12-P02

All values nominal unless tolerances provided; information contained in the present datasheet is subject to confirmation at time of ordering