PRODUCT DATASHEET

# WF-118

Wall feed through (without feed through plate)

These innovative Wall feed through systems feature a design which reduces installation time. Each WF-Kit contains a rubber wall gland which fits inside the mounting plate to hold the coax in place, a butyl sealing compound and a tension clamp with two bolts.

FEATURES / BENEFITS



External Document Links

Installation Instruction

Notes

## Technical features

### STRUCTURE

| | | |
|---|---|---|
| **Product Line** | | Coaxial Cable Accessories |
| **Product Type** | | Wall/Roof Feed-Through System |
| **Feed-Through Component** | | Single Entry Kit |
| **Transmission Line Type** | | HCA118 |
| **Coaxial Cable Type** | | Air Dielectric |
| **Cable Size** | | 1-1/8" |

### MECHANICAL SPECIFICATIONS

| | | |
|---|---|---|
| **Feed-Through Holes** | | 1 |
| **Feed-Through Hole Diameter** | mm (in) | 55 (2.17) |
| **Mated to Cable Size and Interface** | | 1-1/8 |

### PACKAGING INFORMATION

| | | |
|---|---|---|
| **Package Quantity** | | 1 |



All values nominal unless tolerances provided; information contained in the present datasheet is subject to confirmation at time of ordering